



VD – 621	
<i>Image Pickup Device</i>	1/3" SONY Colour CCD
<i>Resolution</i>	540 TV Lines
<i>Pixels</i>	~ 470K
<i>Lens</i>	3~9 mm
<i>Video Output</i>	1.0 Vp-p 75ohm (BNC type)
<i>Audio Output</i>	-
<i>Alarm Input / Output</i>	-
<i>Iris Control</i>	A.E.S/DD On/Off (selectable)
<i>Shutter Mode</i>	1/50 ~ 1/100,000 sec.
<i>S/N Ratio</i>	52dB(min.) / 60dB(typ.) (AGC off)
<i>Gamma Characteristic</i>	0.45
<i>Scanning System & Frequency</i>	625 Lines, 50 Field/sec.
<i>Gain Control & White Balance</i>	Gain Control : Auto/ On/Off (selectable) White Balance : Mode :ATW/ AWB (0 Colour Rolling) Range: 3200~10000°K
<i>Backlight Mode</i>	Auto/ On/Off (selectable)
<i>Minimum Illumination</i>	0.015 Lux (F:1.4) 3200°K (20IRE) (Sense UP max.)
<i>Day / Night Function</i>	-
<i>IR Sensitive</i>	-
<i>IR LED</i>	-
<i>IR Coverage / Viewing Range (approximate)</i>	-
<i>Pan / Tilt Angle (approximate)</i>	Pan : 0~45° , Tilt : 0~90°
<i>Pan / Tilt Speed (approximate)</i>	-
<i>Image Masking</i>	-
<i>Aperture Suppress</i>	-
<i>Flickerless</i>	-
<i>Sharpness</i>	-
<i>Built Special Function</i>	Digital Noise Reduction: S/N up 4.5dB, Sense UP: On/Off (Preset x4, Option x32)
<i>Network / Remote Control</i>	-
<i>Presets</i>	-
<i>Users</i>	-
<i>Video Resolution & Speed</i>	-
<i>Image Quality</i>	-
<i>Power Supply & Consumption</i>	DC12V 150mA
<i>Operation Temperature & Humidity</i>	-20°C ~ +50°C ; RH 95% (max.)
<i>Storage Temperature</i>	-20°C ~ +60°C ; RH 95% (max.)
<i>Dimension (w/o bracket) (approximate)</i>	130(Φ) x 95(h) mm
<i>Weight (w/o bracket) (approximate)</i>	250 g

** Design & specification are subject to change without prior notice **