



(Rear view)

**Model**

**VDR-1621EL**

**Operation type**

Triplex (Local Record, Local Playback, Remote Playback/Record/Remote View)

**Video Input / Output**

In: 16xBNC, Out: 2xBNC

**Display Mode**

1/ 4/ 9/ 16 ch.

**Resolution (max.)**

Display: 720x576, Record: 720x288

**Speed (max.)**

Display: 400 fps.,  
Record: 1/ 2/ 3/ 5/ 10/ 12/ 25 / 50 / 100 fps.

**Playback channel**

1 ch.

**Record Mode**

Manual / Continuous/ Schedule / Motion

**Pre / Post Record Duration**

Post : 10 ~ 99 sec.

**Search Mode**

Time / Date / Event

**Video Compression Format**

Modified Motion JPEG

**Image Quality**

1 ~ 4

**Audio Input & Output**

In: 1xRCA, Out: 1xRCA

**Alarm Input & Output**

In: 4 ch.(Pin),  
Out: 1ch.(Pin) (NC/NO)

**Motion Detection Area & Sensitivity**

Area: 16(H) x 12(V), Sensitivity:1~9

**Privacy Masking**

-

**Console Function**

Auto Recover after power resume, Colour, Hue, Brightness, Contrast, Gain  
2 x (SATA)

**Hardisc Bay**

**USB Interface**

Pendrive, HDD backup

**CDRW / DVDRW**

-

**PTZ Protocol**

Pelco-D, Pelco-P, Baud Rate:1200~19200bps.

**Network & Control Interface**

RJ-45, RS485

**Network Function**

3 users login, Network playback & record, multi display mode

**Remote Software**

Client Software, IE(will prompt to download client software)

**Power Supply & Consumption**

DC12V 5A

**Operation Temperature & Humidity**

10°C ~ 45°C (10%~90%)

**Dimension (approximate)**

430(w) x 55(h) x 300(d) mm

**Weight (w/o Hardisc) (approximate)**

4 kg

\*\* Design & specification are subject to change without prior notice \*\*