



(Rear view)

Model

VDR-1621EL

Operation type

Triplex (Local Record, Local Playback, Remote Playback/Record/Remote View)

Video Input / Output

In: 16xBNC, Out: 2xBNC

Display Mode

1/ 4/ 9/ 16 ch.

Resolution (max.)

Display: 720x576, Record: 720x288

Speed (max.)

Display: 400 fps.,
Record: 1/ 2/ 3/ 5/ 10/ 12/ 25 / 50 / 100 fps.

Playback channel

1 ch.

Record Mode

Manual / Continuous/ Schedule / Motion

Pre / Post Record Duration

Post : 10 ~ 99 sec.

Search Mode

Time / Date / Event

Video Compression Format

Modified Motion JPEG

Image Quality

1 ~ 4

Audio Input & Output

In: 1xRCA, Out: 1xRCA

Alarm Input & Output

In: 4 ch.(Pin),
Out: 1ch.(Pin) (NC/NO)

Motion Detection Area & Sensitivity

Area: 16(H) x 12(V), Sensitivity:1~9

Privacy Masking

-

Console Function

Auto Recover after power resume, Colour, Hue, Brightness, Contrast, Gain
2 x (SATA)

Hardisc Bay

USB Interface

Pendrive, HDD backup

CDRW / DVDRW

-

PTZ Protocol

Pelco-D, Pelco-P, Baud Rate:1200~19200bps.

Network & Control Interface

RJ-45, RS485

Network Function

3 users login, Network playback & record, multi display mode

Remote Software

Client Software, IE(will prompt to download client software)

Power Supply & Consumption

DC12V 5A

Operation Temperature & Humidity

10°C ~ 45°C (10%~90%)

Dimension (approximate)

430(w) x 55(h) x 300(d) mm

Weight (w/o Hardisc) (approximate)

4 kg

** Design & specification are subject to change without prior notice **