



(Rear view)

<i>Model</i>	VDR-1622L
<i>Operation type</i>	Triplex (Local Record, Local Playback, Remote Playback/Record/Remote View)
<i>Video Input / Output</i>	In: 16x BNC, Out: 2x Monitor/Spot (BNC), 1x VGA, 16x LoopOut (BNC)
<i>Display Mode</i>	1 / 4 / 9 / 16 ch.
<i>Resolution (max.)</i>	Display: 720x576, Record: 720x576
<i>Speed (max.)</i>	Display: 400 fps., Record: <b>D1</b> :25fps. / <b>HD1</b> :50fps. / <b>CIF</b> :100fps.
<i>Playback channel</i>	1 / 4 / 8 / 13 / Quad
<i>Record Mode</i>	Manual / Continuous / Schedule / Motion
<i>Pre / Post Record Duration</i>	Pre: 0~4 sec., Post : 5 ~ 99 sec.
<i>Search Mode</i>	Time / Date / Event
<i>Video Compression Format</i>	MPEG-4
<i>Image Quality</i>	1 ~ 4
<i>Audio Input &amp; Output</i>	In: 4x RCA, Out: 1x RCA
<i>Alarm Input &amp; Output</i>	In: 16 ch.(Pin), Out: 1ch.(Pin) (NC/NO)
<i>Motion Detection Area &amp; Sensitivity</i>	Area: 29(H) x 24(V), Sensitivity: 1~8
<i>Privacy Masking</i>	-
<i>Console Function</i>	Auto Recover after power resume, Colour, Hue, Brightness, Contrast, Gain
<i>Hardisc Bay</i>	2 x (SATA) / (IDE)
<i>USB Interface</i>	PC Mouse, Pendrive, HDD backup
<i>CDRW / DVDRW</i>	1 x DVD-RW
<i>PTZ Control</i>	<b>Protocol:</b> Pelco-D, Pelco-P, Mikami; <b>Address:</b> 0~255; <b>Presets:</b> 20; <b>Baud Rate:</b> 1200~19200bps.
<i>Network &amp; Control Interface</i>	RJ-45, RS485
<i>Network Function</i>	Network view w/audio, playback, PTZ control
<i>Remote Software</i>	Client Software, I.E. (download Client Software)
<i>Power Supply &amp; Consumption</i>	DC12V 5A
<i>Operation Temperature &amp; Humidity</i>	10°C ~ 45°C (10%~90%)
<i>Dimension (approximate)</i>	430(w) x 100(h) x 385(d) mm
<i>Weight (w/o Hardisc) (approximate)</i>	6 kg

\*\* Design & specification are subject to change without prior notice \*\*