



(Rear view)

Model	VDR-316
<b>Operation type</b>	Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)
<b>Video Input / Output</b>	In: 16xBNC, Out: 2xBNC, 1xSVideo, 1xVGA
<b>Display Mode</b>	1 / 4 / 9 / 16 ch.
<b>Resolution (max.)</b>	Display: 720x576, Record: 360x288
<b>Speed (max.)</b>	Display: 400 fps, Record: 200 fps
<b>Playback channel</b>	1 / 4 ch.
<b>Record Mode</b>	Manual / Timer / Motion / Alarm
<b>Pre / Post Record Duration</b>	Pre: 4 sec., Post : 10 ~ 60 sec.
<b>Search Mode</b>	Time / Date / Event
<b>Video Compression Format</b>	H.264
<b>Image Quality</b>	Lowest / Lower / Medium / Higher / Highest
<b>Audio Input &amp; Output</b>	In: 4xRCA, Out: 1xRCA
<b>Alarm Input &amp; Output</b>	In: 16 ch.(Terminal), Out: 4ch.(Terminal) (NC/NO)
<b>Motion Detection Area &amp; Sensitivity</b>	Area: 27(H) x 23(V), Sensitivity:1~8
<b>Privacy Masking</b>	-
<b>Console Function</b>	Auto Recover after power resume, TV display adjust, Colour, Hue, Brightness, Contrast, 4ch Audio record & playback audio 1ch., Motion/Alarm can trigger PTZ
<b>Hardisc Bay</b>	2 x (SATA)
<b>USB Interface</b>	Pendrive, Hardisc Backup, PC Mouse (for control/setting)
<b>CDRW / DVDRW</b>	1 x DVD-RW(SATA)
<b>PTZ Protocol</b>	10 types, 255 Address, 128 Presets
<b>Network &amp; Control Interface</b>	RJ-45, RS232
<b>Network Function</b>	2 users login, DHCP, PPPoE, DDNS
<b>Remote Software</b>	I.E., Client Software
<b>Power Supply &amp; Consumption</b>	DC12V 4A
<b>Operation Temperature &amp; Humidity</b>	10°C ~ 45°C (10%~90%)
<b>Dimension (approximate)</b>	425(w) x 68(h) x 385(d) mm
<b>Weight (w/o Hardisc) (approximate)</b>	4 kg

\*\* Design & specification are subject to change without prior notice \*\*