



(Rear view)

Model	VDR-316
Operation type	Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)
Video Input / Output	In: 16xBNC, Out: 2xBNC, 1xSVideo, 1xVGA
Display Mode	1 / 4 / 9 / 16 ch.
Resolution (max.)	Display: 720x576, Record: 360x288
Speed (max.)	Display: 400 fps, Record: 200 fps
Playback channel	1 / 4 ch.
Record Mode	Manual / Timer / Motion / Alarm
Pre / Post Record Duration	Pre: 4 sec., Post : 10 ~ 60 sec.
Search Mode	Time / Date / Event
Video Compression Format	H.264
Image Quality	Lowest / Lower / Medium / Higher / Highest
Audio Input & Output	In: 4xRCA, Out: 1xRCA
Alarm Input & Output	In: 16 ch.(Terminal), Out: 4ch.(Terminal) (NC/NO)
Motion Detection Area & Sensitivity	Area: 27(H) x 23(V), Sensitivity:1~8
Privacy Masking	-
Console Function	Auto Recover after power resume, TV display adjust, Colour, Hue, Brightness, Contrast, 4ch Audio record & playback audio 1ch., Motion/Alarm can trigger PTZ
Hardisc Bay	2 x (SATA)
USB Interface	Pendrive, Hardisc Backup, PC Mouse (for control/setting)
CDRW / DVDRW	1 x DVD-RW(SATA)
PTZ Protocol	10 types, 255 Address, 128 Presets
Network & Control Interface	RJ-45, RS232
Network Function	2 users login, DHCP, PPPoE, DDNS
Remote Software	I.E., Client Software
Power Supply & Consumption	DC12V 4A
Operation Temperature & Humidity	10°C ~ 45°C (10%~90%)
Dimension (approximate)	425(w) x 68(h) x 385(d) mm
Weight (w/o Hardisc) (approximate)	4 kg

** Design & specification are subject to change without prior notice **