



(Rear view)

Model	VDR-401S
Operation type	Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)
Video Input / Output	In: 4xBNC, Out: 2xBNC, 1xVGA
Display Mode	1 / 4 ch.
Resolution (max.)	Display: 704x576, Record: D1 :704x576, CIF :352x288
Speed (max.)	Display: 100 fps, Record: D1 :1~6fps (Total:24fps), CIF :1~25fps (Total:100fps)
Playback channel	1 ch.
Record Mode	Manual / Timer / Motion / Alarm
Pre / Post Record Duration	Pre: 1 ~ 30 sec., Post : 10 ~ 300 sec.
Search Mode	Time / Date / Motion / Alarm
Video Compression Format	H.264
Image Quality	VBR : 1 ~ 6
Audio Input & Output	In: 4xRCA, Out: 2xRCA
Alarm Input & Output	In: 4 ch.(Pin), Out: 2ch.(Pin) (NC/NO)
Motion Detection Area & Sensitivity	Area: 16(H) x 12(V), Sensitivity:1~6
Privacy Masking	1 Areas
Console Function	Auto Recover after power resume, Hardisc redundant, TV display adjust, Colour, Hue, Brightness, Contrast, Gain, White Level, Email/Pop-up message/Relay out/PTZ/Ch.Rec. for any triggered events, Each channel can choose to record Audio+Video or only Audio/Video
Hardisc Bay	1 x (SATA)
USB Interface	Pendrive, Hardisc Backup, PC Mouse (for control/setting)
CDRW / DVDRW	-
PTZ Protocol	34 types, Baud Rate:1200~115200bps.
Network & Control Interface	RJ-45, RS232
Network Function	10 users login, full function of DVR settings, DHCP, PPPoE, DDNS, NTP, Multicast, Email, Alarm Server, FTP
Remote Software	I.E., Client Software
Power Supply & Consumption	DC12V 4A
Operation Temperature & Humidity	10°C ~ 45°C (10%~90%)
Dimension (approximate)	375(w) x 60(h) x 290(d) mm
Weight (w/o Hardisc) (approximate)	4 kg

** Design & specification are subject to change without prior notice **