

# VZOR

## 4 ch. DVR



(Rear view)

Model	VDR-403C
Operation type	Simplex (Record or Playback)
Video Input / Output	In: 4xBNC, Out: 2xBNC
Display Mode	1/4 ch.
Resolution (max.)	Display: 720 x 576, Record: 640*272
Speed (max.)	Display: 100 fps., Record: 25 fps.(Quad), 6.25 fps(Each)
Playback channel	1 ch.
Record Mode	Manual / Schedule / Motion(Each/All) / Sensor(Each/All)
Pre / Post Record Duration	-
Search Mode	Time / Date / Event
Video Compression Format	Advanced MJPEG
Image Quality	Low / Normal / High
Audio Input & Output	In: 1xRCA, Out: 1xRCA
Alarm Input & Output	In: 4 ch.(Pin), Out: 1ch.(Pin)(NC/NO)
Motion Detection Area & Sensitivity	Sensitivity: 1 ~ 5
Privacy Masking	-
Console Function	Auto Recover after power resume, Keylock, Buzzer sound for Video Loss & Motion sensor, Playback frame by frame, Resume recording after exited Menu, Remote Controller, Fan, Contrast, Brightness, Colour
Hardisc Bay	1 x IDE (Tray) – Anti Shock HDD Tray
USB Interface	Hardisc Backup, AVI, MYS, JPEG
CDRW / DVDRW	-
PTZ Protocol	-
Network & Control Interface	-
Network Function	-
Remote Software	-
Power Supply & Consumption	DC12V 1.5A
Operation Temperature & Humidity	10°C ~ 55°C (10% ~ 90%)
Dimension (approximate)	252(w) x 65(h) x 195(d) mm
Weight (w/o Hardisc) (approximate)	2.8 kg

\*\* Design & specification are subject to change without prior notice \*\*