



Model	VDR – 404D1
<b>Operation type</b>	Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)
<b>Video Input / Output</b>	<b>In:</b> 4xBNC, <b>Out:</b> 1xBNC, 1xVGA, 1xHDMI
<b>Display Mode</b>	1/ 4 ch.
<b>Resolution</b>	<b>Display:</b> (Video)704x576, (VGA)1920x1080/ 1280x1024/ 1280x720/ 1024x768 <b>Record:</b> (D1)704x576, (HD1)704x288, (2CIF)352x576, (CIF)352x288, (QCIF)176x144
<b>Speed (max.)</b>	<b>Display:</b> 100 fps., <b>Record:</b> D1/ HD1/ 2CIF/ CIF/ QCIF :1~25fps (each ch.)
<b>Playback channel</b>	1/ 4 ch.
<b>Record Mode</b>	Manual / Timer / Motion / Alarm
<b>Pre / Post Record Duration</b>	Pre: 0 ~ 30 sec., Post : 1 ~ 300 sec.
<b>Search Mode</b>	Time / Date / Motion / Alarm
<b>Video Compression Format</b>	H.264
<b>Image Quality</b>	(VBR):1~6; (VBR/CBR):Main :768~4096Kbs, Extra: 48~256Kbs
<b>Audio Input &amp; Output</b>	In: 4xBNC, Out:1xBNC
<b>Alarm Input &amp; Output</b>	-
<b>Motion Detection Area &amp; Sensitivity</b>	Area: 22(H) x 18(V), Sensitivity:1~6
<b>Privacy Masking</b>	4 Areas (Each channel, during preview / monitoring)
<b>Console Function</b>	Display/Channel/Camera/Hardisc, Auto Recover after power resume, Each channel Audio & Video individual setting, Extra Stream for remote viewing
<b>Hardisc Bay</b>	1 x (SATA)
<b>USB Interface</b>	Pendrive, Hardisc Backup, PC Mouse (for control/setting)
<b>CDRW / DVDRW</b>	-
<b>PTZ Protocol</b>	-
<b>Network &amp; Control Interface</b>	RJ-45
<b>Network Function</b>	Multi-users login, full function of DVR settings, DHCP, PPPoE, DDNS, NTP, Multicast, Email,, FTP, Upgrade Function
<b>Remote Software</b>	I.E., PSS
<b>Power Supply &amp; Consumption</b>	AC 100~240V
<b>Operation Temperature &amp; Humidity</b>	10°C ~ 45°C (10%~90%)
<b>Dimension (approximate)</b>	326 (w) x 50 (h) x 260 (d) mm
<b>Weight (w/o Hardisc) (approximate)</b>	1.3 kg

\*\* Design & specification are subject to change without prior notice \*\*