

VZOR

4 ch. DVR



c/w Remote Control



VDR-405ER / VDR-406ER

(Rear view)



VDR-405ELR

(Rear view)

c/w Network

Model	VDR-405ELR	VDR-405ER	VDR-406ER
Operation type	Triplex (Playback, Record, Network View / Setting / Playback)		Duplex (Playback, Record)
Video Input / Output	In: 4xBNC, Out: 1xBNC		
Display Mode	1 ch.		
Resolution	Display: 720 x 576, Record: 640*272		Display: 640 x 544, Record: 640*272
Display Speed (max.)	Display: 100 fps., Record: 25 fps.		Display: 100 fps., Record: 1~25 fps.(each ch.), Total:50fps.
Playback channel	1 ch.		
Record Mode	Manual / Schedule / Motion		
Pre / Post Record Duration	Post: 10 sec.		Post: 5 ~ 30 sec.
Search Mode	Time / Date / Event		
Video Compression Format	Local: Advanced MJPEG, Network: MPEG4	Modified MJPEG	
Image Quality	Low / Normal / High		Normal / High / Highest
Audio Input & Output	In: 1xRCA, Out: 1xRCA		
Alarm Input & Output	-		
Motion Detection Area & Sensitivity	Sensitivity: 1~9		Sensitivity: 1 ~ 4
Privacy Masking	-		
Console Function	Auto Recover after power resume, Video Loss, Hide Live Display, Remote Controller, Fan, Contrast, Brightness, Colour, Dwell time, Camera On/Off		
Hardisc Bay	1 x (IDE)	1 x (SATA)	
USB Interface	Pendrive, Hardisc Backup, VVF		
CDRW / DVDRW	-		
PTZ Protocol	-		
Network & Control Interface	RJ-45		-
Network Function	3 users with same username+password login, backup to PC thru network, Playback & record Audio+Video ,		-
Remote Software	I.E.		-
Power Supply & Consumption	DC12V 4A		
Operation Temperature & Humidity	-10°C ~ 55°C (10% ~ 90%)		
Dimension (approximate)	220(w) x 50(h) x 290(d) mm		
Weight (w/o Hardisc) (approximate)	1.5 kg		

** Design & specification are subject to change without prior notice **