

VZOR

4 ch. DVR



c/w Remote Control



VDR-405ER / VDR-406ER

(Rear view)



VDR-405ELR

(Rear view)

c/w Network

| Model | VDR-405ELR | VDR-405ER | VDR-406ER |
|--|---|----------------|--|
| Operation type | Triplex (Playback, Record, Network View / Setting / Playback) | | Duplex (Playback, Record) |
| Video Input / Output | In: 4xBNC, Out: 1xBNC | | |
| Display Mode | 1 ch. | | |
| Resolution | Display: 720 x 576, Record: 640*272 | | Display: 640 x 544, Record: 640*272 |
| Display Speed (max.) | Display: 100 fps., Record: 25 fps. | | Display: 100 fps., Record: 1~25 fps.(each ch.), Total:50fps. |
| Playback channel | 1 ch. | | |
| Record Mode | Manual / Schedule / Motion | | |
| Pre / Post Record Duration | Post: 10 sec. | | Post: 5 ~ 30 sec. |
| Search Mode | Time / Date / Event | | |
| Video Compression Format | Local: Advanced MJPEG, Network: MPEG4 | Modified MJPEG | |
| Image Quality | Low / Normal / High | | Normal / High / Highest |
| Audio Input & Output | In: 1xRCA, Out: 1xRCA | | |
| Alarm Input & Output | - | | |
| Motion Detection Area & Sensitivity | Sensitivity: 1~9 | | Sensitivity: 1 ~ 4 |
| Privacy Masking | - | | |
| Console Function | Auto Recover after power resume, Video Loss, Hide Live Display, Remote Controller, Fan, Contrast, Brightness, Colour, Dwell time, Camera On/Off | | |
| Hardisc Bay | 1 x (IDE) | 1 x (SATA) | |
| USB Interface | Pendrive, Hardisc Backup, VVF | | |
| CDRW / DVDRW | - | | |
| PTZ Protocol | - | | |
| Network & Control Interface | RJ-45 | | - |
| Network Function | 3 users with same username+password login, backup to PC thru network, Playback & record Audio+Video , | | - |
| Remote Software | I.E. | | - |
| Power Supply & Consumption | DC12V 4A | | |
| Operation Temperature & Humidity | -10°C ~ 55°C (10% ~ 90%) | | |
| Dimension (approximate) | 220(w) x 50(h) x 290(d) mm | | |
| Weight (w/o Hardisc) (approximate) | 1.5 kg | | |

** Design & specification are subject to change without prior notice **