



(Rear view)

Model	VDR – 414MR
Operation type	Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)
Video Input / Output	In: 4xBNC, Out: 1xBNC, 1xVGA
Display Mode	1/ 4 ch.
Resolution (max.)	Display: (VGA) 1280x1024/ 1024x768/ 800x600, Record: 704x576
Speed (max.)	Display: 100 fps, Record: D1 / HD1 / CIF : 1~25fps (Total:100fps)
Playback channel	1/ 4 ch
Record Mode	Normal / Motion / Sensor
Pre / Post Record Duration	Pre: 3 sec., Post : 2/5/10/15 min.
Search Mode	Time / Date / Motion / Sensor/ All
Video Compression Format	H.264
Image Quality	Good/ Better/ Best
Audio Input & Output	In: 4xBNC, 1xMic In, Out:1xBNC, 1xSpeaker Out
Alarm Input & Output	In: 4 ch.(Pin), Out: 1ch.(Pin) (N.O.)
Motion Detection Area & Sensitivity	Area: 22 (H) x 18 (V), Sensitivity: Lowest/ Low/ Medium/ High
Privacy Masking	4 Areas (Adjustable)
Console Function	Adjust settings for TV/Display, Recording, Audio, Alarm, PTZ, Network, User account, Firmware upgrade, Live Monitoring + Playback simultaneously at different screen (Video+VGA Output)
Hardisc Bay	1 x (SATA)
USB Interface	Pendrive, Hardisc Backup, PC Mouse (for control/setting)
CDRW / DVDRW	-
PTZ Protocol	22 types, Baud Rate:1200~38400bps.
Network & Control Interface	RJ-45, RS232, RS485
Network Function	30-users login, full function of DVR settings, DHCP, PPPoE, DDNS
Remote Software	I.E., Client Software (Windows & Mac)
Power Supply & Consumption	DC12V 3A
Operation Temperature & Humidity	10°C ~ 45°C (10%~95%)
Dimension (approximate)	250 (w) x 50 (h) x 270 (d) mm
Weight (w/o Hardisc) (approximate)	1.35 Kg

** Design & specification are subject to change without prior notice **