



(Rear view)

Model	VDR-804M
<b>Operation type</b>	Triplex (Local Record, Local Playback, Remote Playback/Record/Remote View)
<b>Video Input / Output</b>	In: 4xBNC, Out: 2xBNC
<b>Display Mode</b>	1/ 4 ch.
<b>Resolution (max.)</b>	Display: 704x576, Record: <b>HD1</b> :704x288, <b>CIF</b> :352x288
<b>Speed (max.)</b>	Display: 100 fps., Record: 1/ 2/ 3.5/ 4.1/ 5/ 6.2/ 8.3/ 12.5/ 25 fps.
<b>Playback channel</b>	1/ 4 ch.
<b>Record Mode</b>	Manual / Continuous/ Motion
<b>Pre / Post Record Duration</b>	-
<b>Search Mode</b>	Time / Date / Event/ Percentage
<b>Video Compression Format</b>	MJPEG
<b>Image Quality</b>	Lowest/ Low/ Normal/ High/ Highest
<b>Audio Input &amp; Output</b>	-
<b>Alarm Input &amp; Output</b>	In: 4 ch.(Pin), Out: 2ch.(Pin) (NC/NO)
<b>Motion Detection Area &amp; Sensitivity</b>	Area: 16(H) x 12(V), Sensitivity:1~5
<b>Privacy Masking</b>	-
<b>Console Function</b>	Auto Recover after power resume, PIP, Digital zoom, Colour, Hue, Brightness, Contrast, Gain, CF/SD card flash player
<b>Hardisc Bay</b>	1 x (IDE)
<b>USB Interface</b>	-
<b>CDRW / DVDRW</b>	1 x CDRW
<b>PTZ Protocol</b>	-
<b>Network &amp; Control Interface</b>	RJ-45
<b>Network Function</b>	1 user login, Network playback & record
<b>Remote Software</b>	Client Software
<b>Power Supply &amp; Consumption</b>	DC12V 5A
<b>Operation Temperature &amp; Humidity</b>	10°C ~ 45°C (10%~90%)
<b>Dimension (approximate)</b>	195(w) x 180(h) x 200(d) mm
<b>Weight (w/o Hardisc) (approximate)</b>	4 kg

\*\* Design & specification are subject to change without prior notice \*\*