



(Rear view)

Model	VDR-861L
Operation type	Triplex (Local Record, Local Playback, Remote Playback/Record/Remote View)
Video Input / Output	In: 8xBNC, Out: 2xBNC, 1xVGA
Display Mode	1/ 4/ 9 ch.
Resolution (max.)	Display: 640x544, (VGA)1280x1024/ 1280x720/ 1024x768/ 800x600 Record: 640x272
Speed (max.)	Display: 200 fps., Record: 1/ 2/ 3/ 5/ 10/ 12/ 25 / 50 fps.
Playback channel	1 ch.
Record Mode	Manual / Continuous / Schedule / Motion
Pre / Post Record Duration	Post : 10 ~ 99 sec.
Search Mode	Time / Date / Event
Video Compression Format	Modified Motion JPEG/ MPEG4
Image Quality	Highest / High / Normal
Audio Input & Output	In: 4xRCA, Out: 1xRCA
Alarm Input & Output	In: 8 ch.(Pin), Out: 1ch.(Pin) (NC/NO)
Motion Detection Area & Sensitivity	Area: 16(H) x 12(V), Sensitivity:1~4
Privacy Masking	-
Console Function	Auto Recover after power resume, Colour, Hue, Brightness, Contrast, Saturation
Hardisc Bay	2 x (SATA)
USB Interface	Pendrive, HDD backup, Firmware upgrade
CDRW / DVDRW	-
PTZ Protocol	Pelco-D, Pelco-P, Merit Lilin, Baud Rate:1200~19200bps.
Network & Control Interface	RJ-45, RS485
Network Function	3 users login, Network playback & record, multi display mode
Remote Software	Client Software, IE(will prompt to download client software)
Power Supply & Consumption	DC12V 4A
Operation Temperature & Humidity	10°C ~ 45°C (10%~90%)
Dimension (approximate)	430(w) x 55(h) x 300(d) mm
Weight (w/o Hardisc) (approximate)	4 kg

** Design & specification are subject to change without prior notice **