



|  | VD – V101                     |
|--|-------------------------------|
| <b>Image Pickup Device</b>                       | 1/3" VZOR Colour CCD          |
| <b>Resolution</b>                                | 450 TV Lines                  |
| <b>Pixels</b>                                    | 752(H) x 582(V)               |
| <b>Lens</b>                                      | 3.5~8 mm                      |
| <b>Video Output</b>                              | 1.0 Vp-p 75ohm (BNC type)     |
| <b>Audio Output</b>                              | -                             |
| <b>Alarm Input / Output</b>                      | -                             |
| <b>Iris Control</b>                              | Manual                        |
| <b>Shutter Mode</b>                              | 1/50 ~ 1/100,000 sec.         |
| <b>S/N Ratio</b>                                 | ≥ 48dB (AGC off)              |
| <b>Gamma Characteristic</b>                      | 0.45                          |
| <b>Scanning System &amp; Frequency</b>           | 625 Lines, 50 Field/sec.      |
| <b>Gain Control &amp; White Balance</b>          | Auto                          |
| <b>Backlight Mode</b>                            | -                             |
| <b>Minimum Illumination</b>                      | 0.8 Lux (F:1.2)               |
| <b>Day / Night Function</b>                      | -                             |
| <b>IR Sensitive</b>                              | -                             |
| <b>IR LED</b>                                    | -                             |
| <b>IR Coverage / Viewing Range (approximate)</b> | -                             |
| <b>Pan / Tilt Angle (approximate)</b>            | Pan : 0~120°, Tilt : 0~80°    |
| <b>Pan / Tilt Speed (approximate)</b>            | -                             |
| <b>Image Masking</b>                             | -                             |
| <b>Aperture Suppress</b>                         | -                             |
| <b>Flickerless</b>                               | -                             |
| <b>Sharpness</b>                                 | -                             |
| <b>Built Special Function</b>                    | -                             |
| <b>Network / Remote Control</b>                  | -                             |
| <b>Presets</b>                                   | -                             |
| <b>Users</b>                                     | -                             |
| <b>Video Resolution &amp; Speed</b>              | -                             |
| <b>Image Quality</b>                             | -                             |
| <b>Power Supply &amp; Consumption</b>            | DC12V 150mA                   |
| <b>Operation Temperature &amp; Humidity</b>      | -10°C ~ +50°C ; RH 95% (max.) |
| <b>Storage Temperature</b>                       | -20°C ~ +60°C ; RH 95% (max.) |
| <b>Dimension (w/o bracket) (approximate)</b>     | 113(Φ) x 80(h) mm             |
| <b>Weight (w/o bracket) (approximate)</b>        | 400 g                         |

\*\* Design & specification are subject to change without prior notice \*\*