



(Rear view)

<i>Model</i>	VDVR-402
<i>Operation type</i>	Duplex (Local Record, Local Playback/Remote Playback/Record/Remote View)
<i>Video Input / Output</i>	In: 4xBNC, Out: 2xBNC, 1xVGA, 1xSVHS, 4xBNC Loop Out
<i>Display Mode</i>	1 / 4 ch.
<i>Resolution (max.)</i>	Display: 704x576, Record: CIF :352x288
<i>Speed (max.)</i>	Display: 100 fps., Record: 25 / 50 / 100 fps.
<i>Playback channel</i>	1 ch.
<i>Record Mode</i>	Manual / Timer / Motion
<i>Pre / Post Record Duration</i>	Post : 1 ~ 180 sec.
<i>Search Mode</i>	Time / Date / Event
<i>Video Compression Format</i>	MJPEG
<i>Image Quality</i>	Low / Medium / High
<i>Audio Input & Output</i>	-
<i>Alarm Input & Output</i>	In: 4 ch.(Pin), Out: 1ch.(Pin) (NC/NO)
<i>Motion Detection Area & Sensitivity</i>	Area: 16(H) x 12(V), Sensitivity:1~10
<i>Privacy Masking</i>	1 Area
<i>Console Function</i>	Auto Recover after power resume, Hardisc redundant, TV display adjust, Colour, Hue, Brightness, Contrast, Gain
<i>Hardisc Bay</i>	1 x (IDE)
<i>USB Interface</i>	-
<i>CDRW / DVDRW</i>	-
<i>PTZ Protocol</i>	Pelco-D, Baud Rate:1200~19200bps.
<i>Network & Control Interface</i>	RJ-45, RS232, RS485
<i>Network Function</i>	1 user login, Network playback & record
<i>Remote Software</i>	Client Software
<i>Power Supply & Consumption</i>	DC12V 5A
<i>Operation Temperature & Humidity</i>	10°C ~ 45°C (10%~90%)
<i>Dimension (approximate)</i>	430(w) x 65(h) x 345(d) mm
<i>Weight (w/o Hardisc) (approximate)</i>	4 kg

** Design & specification are subject to change without prior notice **