



(Rear view)

| Model  | VDVR-402   |
|--|--|
| <b>Operation type</b>                          | Duplex (Local Record, Local Playback/Remote Playback/Record/Remote View)                                       |
| <b>Video Input / Output</b>                    | In: 4xBNC, Out: 2xBNC, 1xVGA, 1xSVHS, 4xBNC Loop Out   |
| <b>Display Mode</b>                            | 1 / 4 ch.  |
| <b>Resolution (max.)</b>                       | Display: 704x576, Record: <b>CIF:352x288</b>   |
| <b>Speed (max.)</b>                            | Display: 100 fps.,<br>Record: 25 / 50 / 100 fps.   |
| <b>Playback channel</b>                        | 1 ch.  |
| <b>Record Mode</b>                             | Manual / Timer / Motion  |
| <b>Pre / Post Record Duration</b>              | Post : 1 ~ 180 sec.  |
| <b>Search Mode</b>                             | Time / Date / Event  |
| <b>Video Compression Format</b>                | MJPEG  |
| <b>Image Quality</b>                           | Low / Medium / High  |
| <b>Audio Input &amp; Output</b>                | -  |
| <b>Alarm Input &amp; Output</b>                | In: 4 ch.(Pin),<br>Out: 1ch.(Pin) (NC/NO)  |
| <b>Motion Detection Area &amp; Sensitivity</b> | Area: 16(H) x 12(V), Sensitivity:1~10  |
| <b>Privacy Masking</b>                         | 1 Area   |
| <b>Console Function</b>                        | Auto Recover after power resume, Hardisc redundant, TV display adjust, Colour, Hue, Brightness, Contrast, Gain |
| <b>Hardisc Bay</b>                             | 1 x (IDE)  |
| <b>USB Interface</b>                           | -  |
| <b>CDRW / DVDRW</b>                            | -  |
| <b>PTZ Protocol</b>                            | Pelco-D, Baud Rate:1200~19200bps.  |
| <b>Network &amp; Control Interface</b>         | RJ-45, RS232, RS485  |
| <b>Network Function</b>                        | 1 user login, Network playback & record  |
| <b>Remote Software</b>                         | Client Software  |
| <b>Power Supply &amp; Consumption</b>          | DC12V 5A   |
| <b>Operation Temperature &amp; Humidity</b>    | 10°C ~ 45°C (10%~90%)  |
| <b>Dimension (approximate)</b>                 | 430(w) x 65(h) x 345(d) mm   |
| <b>Weight (w/o Hardisc) (approximate)</b>      | 4 kg   |

\*\* Design & specification are subject to change without prior notice \*\*