

VZOR

IP Camera



VIB - 102



VIR - 111

| | VIB - 102 | VIR - 111 |
|------------------------------|--|---|
| Image Pickup Device | 1/3" SONY Colour CCD | 1/3" SONY SuperHAD Colour CCD |
| Lens | 3.5 ~ 8 mm (Manual Iris) | 6 mm |
| Horizontal Resolution | 480 TV Line | |
| Pixels | 752(H) x 582(V) | |
| Illumination | 0.1 Lux (Colour); 0.01 Lux (B/W) | 0.3Lux (Colour); 0.03 Lux(B/W); 0 Lux (30*IR LED On) |
| IR Coverage | - | 10 ~ 15m |
| S/N Ratio | > 50dB | |
| Gain Control & White Balance | Manual / Auto | |
| Gamma Correction | 0.45 | |
| Electronic Shutter | 1/50 ~ 1/100,000 sec. | |
| Video Compression | H.264 | |
| Video Resolution | D1 (704*576), 2CIF (704*288), CIF (352*288), QCIF (176*144) | |
| Image Quality | Adjustable Bit Rate | |
| Dual Stream | Yes (1ch.D1-25fps + 1ch. CIF-25fps) | |
| Video Speed | 1 ~ 25 fps. | |
| Audio Input / Output | 1*Audio In, 1*Audio Out. | |
| Alarm Input / Output | 2*Alarm In, 1*Alarm Out. | |
| Network Support / Control | RS485,RS232,RJ45, DHCP, SMTP, DDNS, FTP, TCP/IP, PPPoE, IE, Net AV Live/Record/Playback , Full Camera function, PTZ | |
| User Login | 10 users login simultaneously | |
| Privacy Masking | Yes | |
| Operating Temperature | 0°C ~ +50°C | |
| Humidity | 10 ~ 90% | |
| Power Supply | DC 12V (<6W) | DC 12V (<6W) |
| Dimension (mm) | 70(w) x 65(h) x 165(d) | 75(Ø) x 165(d) |
| Weight (approx.) | 500 g | 500g |

** Design & specification are subject to change without prior notice **