

VZOR

IP Camera



VIB - 102



VIR - 111

	VI B - 102	VIR - 111
Image Pickup Device	1/3" SONY Colour CCD	1/3" SONY SuperHAD Colour CCD
Lens	3.5 ~ 8 mm (Manual Iris)	6 mm
Horizontal Resolution	480 TV Line	
Pixels	752(H) x 582(V)	
Illumination	0.1 Lux (Colour); 0.01 Lux (B/W)	0.3Lux (Colour); 0.03 Lux(B/W); 0 Lux (30*IR LED On)
IR Coverage	-	10 ~ 15m
S/N Ratio	> 50dB	
Gain Control & White Balance	Manual / Auto	
Gamma Correction	0.45	
Electronic Shutter	1/50 ~ 1/100,000 sec.	
Video Compression	H.264	
Video Resolution	D1 (704*576), 2CIF (704*288), CIF (352*288), QCIF (176*144)	
Image Quality	Adjustable Bit Rate	
Dual Stream	Yes (1ch.D1-25fps + 1ch. CIF-25fps)	
Video Speed	1 ~ 25 fps.	
Audio Input / Output	1*Audio In, 1*Audio Out.	
Alarm Input / Output	2*Alarm In, 1*Alarm Out.	
Network Support / Control	RS485,RS232,RJ45, DHCP, SMTP, DDNS, FTP, TCP/IP, PPPoE, IE, Net AV Live/Record/Playback , Full Camera function, PTZ	
User Login	10 users login simultaneously	
Privacy Masking	Yes	
Operating Temperature	0°C ~ +50°C	
Humidity	10 ~ 90%	
Power Supply	DC 12V (<6W)	DC 12V (<6W)
Dimension (mm)	70(w) x 65(h) x 165(d)	75(Ø) x 165(d)
Weight (approx.)	500 g	500g

** Design & specification are subject to change without prior notice **