

# VZOR

## Megapixel IP Camera



\* Lens not included



	<b>VI B – 901X</b>
<i>Image Pickup Device</i>	1/3" MICRON Colour CMOS Chipset
<i>Lens</i>	-
<i>Horizontal Resolution</i>	-
<i>Pixels</i>	1600(H) x 1200(V)
<i>Illumination</i>	0.1 Lux (F1.2)
<i>Day /Night</i>	Yes
<i>S/N Ratio</i>	> 50dB
<i>Gain Control &amp; White Balance</i>	Manual / Auto
<i>Gamma Correction</i>	0.45
<i>Electronic Shutter</i>	1/50 ~ 1/10000 sec.
<i>Video Compression</i>	H.264
<i>Video Resolution</i>	UXGA(1600x1200), WSXGA(1600x1024), SXGA(1280x1024), WXGA(1280x800), XVGA(1024x768), SVGA(800x600), VGA(640x480), QVGA(320x240), QQVGA(160x120); D1(704*576), HD1(352*576), CIF (352*288), QCIF (176*144)
<i>Image Quality</i>	Adjustable Bit Rate (32K ~ 8Mbps)
<i>Dual Stream</i>	(Main) UXGA,WSXGA,SXGA,WXGA,XVGA : 1~15fps, Others : 1~25fps; (Extra) D1/HD1/CIF/QCIF/VGA/QVGA/QQVGA : 1~25FPS
<i>Video Input / Output</i>	1*Video Output (1Vp-p)
<i>Audio Input / Output</i>	1*Audio In, 1*Audio Out.
<i>Alarm Input / Output</i>	2*Alarm In, 1*Alarm Out.
<i>Network Support / Control</i>	RS485,RS232,RJ45, DHCP, SMTP, DDNS, FTP, TCP/IP, PPPoE, IE, Net AV Live/Record/Playback , Full Camera function, PTZ
<i>User Login</i>	10 users login simultaneously
<i>Privacy Masking</i>	Yes
<i>Operating Temperature</i>	0°C ~ +50°C
<i>Humidity</i>	10 ~ 90%
<i>Power Supply</i>	DC 12V ( <6W)
<i>Dimension (mm)</i>	70(w) x 65(h) x 165(d)
<i>Weight (approx.)</i>	500 g

\*\* Design & specification are subject to change without prior notice \*\*