



Model	ViDR – 401L
Operation type	Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)
Video Input / Output	Out: 1xBNC, 1xVGA, 1xHDMI
Display Mode	1/ 4ch.
Resolution (max.)	Display: depend on IP camera's settings, Record: depend on IP camera's settings (max. 1.3M pixel)
Speed (max.)	Display: 100fps., Record: depend on IP camera's settings (max. 1.3M pixel)
Playback channel	4 ch.
Record Mode	Timer/ Alarm/ Motion
Pre / Post Record Duration	-
Search Mode	Timer/ Alarm
Video Compression Format	H.264
Image Quality	Base on Schedule, Alarm, Motion setup
Audio Input & Output	In: 1xMic In(BNC), Out: 1xMic Out(BNC)
Alarm Input & Output	In: 4 ch.(Pin), Out: 4ch.(Pin)
Motion Detection Area & Sensitivity	-
Privacy Masking	-
Console Function	Backup video with water mark, Partial display enlargement, Auto Recover after power resume, Hardisc redundant, TV display adjust, PTZ, Each channel individual Audio/Video settings, Main/ Extra Stream for recording/playback
Hardisc Bay	4 x (SATA) (max.)
USB Interface	Pendrive, Hardisc Backup, PC Mouse (for control/setting)
CDRW / DVDRW	1xDVDRW (optional)
PTZ Protocol	-
Network & Control Interface	RJ-45, RS232, RS485
Network Function	10 users login simultaneously (max.)
Remote Software	I.E. , CMS software
Power Supply & Consumption	AC 100~240V
Operation Temperature & Humidity	10°C ~ 45°C (10%~90%)
Dimension (approximate)	440(w) x 80(h) x 450(d) mm
Weight (w/o Hardisc) (approximate)	5 kg

** Design & specification are subject to change without prior notice **