

HD

ViDR - XX03 series

Network Video Recorder



- > **Up to 8/16/32 channel with 1080P realtime live view**
- > **H.264/MJPEG dual codec decoding**
- > **Up to 5MP resolution**
- > **Max 160Mbps incoming bandwidth**
- > **HDMI / VGA simultaneous video output**
- > **8/16/32 channel synchronous realtime preview, GRID interface**
- > **Support Multi-brand network cameras: eg: Vzor, Sony, Vivotek, Pelco, Samsung, etc**
- > **ONVIF Version 2.0 conformance**
- > **3D intelligent positioning with VZOR PTZ camera**
- > **Support 8 SATA HDDs up to 32TB, 1 eSATA, 4 USB2.0**
- > **Multiple network monitoring: Web viewer, VZOR Hybrid IP Station (CMS) & DMSS**

Model	ViDR-0803	ViDR-1603	ViDR-3203
System			
Main Processor	Dual-core embedded processor		
Operating System	Embedded LINUX		
Video & Audio			
IP Camera Input	8 channel	16 channel	32 channel
Two-way Talk	1 channel Input, 1 channel Output, BNC		
Display			
Interface	1 HDMI, 1 VGA, 1TV		
Resolution	1920x1080, 1280x1024, 1280x720, 1024x768		
Display Split	1/4/8/9	1/4/8/9/16	1/4/8/9/16/25/36
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording		
Recording			
Compression	H.264 / MJPEG		
Resolution	5MP(2560x1920) / 3MP(2048x1536) / 1080P(1920x1080) / 720P(1280x720) / D1 (704x576/704x480) & etc.		
Record Rate	Max 192Mbps		
Bit Rate	48~ 8192kbps		
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop		
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec		
Video Detection & Alarm			
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer & Screen tips		
Video Detection	Motion Detection, MD Zones: 396(22x18), Video Loss & Camera Blank		
Alarm Input	8 channel	16 channel	16 channel
Relay Output	6 channel		

Playback & Backup			
Sync Playback	1/4/9ch	1/4/9/16	1/4/9/16
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search		
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom		
Backup Mode	USB Device / eSATA Device / Internal SATA burner/ Network		
Network			
Ethernet	2 RJ-45 port (10/100/1000Mbps)		
PoE	n/a		
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search(Support Dahua IP camera, DVR, NVS and etc.)		
Max. User Access	128 users		
Smart Phone	iPhone, iPad, Android, Windows Phone		
Storage			
Internal HDD	8 SATA ports (8HDDs or 6HDDs+1CD/DVD-RW), up to 32TB Total Storage		
External HDD	1 eSATA port		
Auxiliary Interface			
USB	4 ports (2 Rear), USB2.0		
RS232	1 port, For PC communication & Keyboard		
RS485	1 port, For PTZ control		
General			
Power Supply	AC 100V~240V, 50/60Hz		
Power Consumption	75W (without HDD)		
Working Environment	-10℃~+55℃ / 10%~90%RH / 86~106kpa		
Dimension (WxDxH)	2U , 440 x 460 x 89 mm		
Weight	6KG (without HDD)		

** Specifications & Product outlooks are subject to change without prior notice **