

VZOR**4 ch.Nightvision IP Camera + DVR Package**

*** Prefixed IP**
**** Plug & Play**



(Rear view)

Model**Operation type****Video Input / Output****Display Mode****Resolution (max.)****Speed (max.)****Playback channel****Record Mode****Pre / Post Record Duration****Search Mode****Video Compression Format****Image Quality****Audio Input & Output****Alarm Input & Output****Motion Detection Area & Sensitivity****Privacy Masking****Console Function****Hardisc Bay****USB Interface****CDRW / DVDRW****PTZ Protocol****Network & Control Interface****Network Function****Remote Software****Power Supply & Consumption****Operation Temperature & Humidity****Dimension (approximate)****Weight (w/o Hardisc) (approximate)****VIH – 200K (NVR)**

Pentaplex (Local Record, Local Playback/Local Settings, Remote Playback/Record, Remote View, Remote Settings)

Out: 1xVGA, 1xHDMI

1/ 4 ch.

Display: (VGA) 1920*1080/ 1440*900/1280*1024/ 1280*960/ 1280*720/ 1024*768

Record: (Main) 4*720p (1280*720);

Display: 100 fps,

Record: (Main) 1~25fps;

1/ 4 ch

Always / Motion / Schedule

Pre: On/ Off ; Post: 30~300 sec.

Normal/ Alarm/ Motion/ Time/ Date/ Ch.

H.264

Very Low/ Low/ Normal/ High/ Very High

In: 1xRCA, Out: 1xRCA

In: 4xPin, Out: 1xPin(N.O.)

Area: 20x12, **Sensitivity:** Normal/ Good/ Better/ Best

-

Individual IP Camera setting, Auto Recover after power resume, Video Loss, Remote Controller, Contrast, Brightness, Colour, Dwell time, Camera On/Off

1 x (SATA)

2xPorts (Ext.HDD, Pendrive backup, PC Mouse, Upgrade)

-

Protocol: Pelco-D/ Pelco-P, Baud Rate: 1200~115200

RS485

NTP, Static, DHCP, PPPoE, FTP, DDNS, PTZ

I.E, CMS

DC12V 4.16A

10°C ~ 45°C (10%~90%)

300(w) x 50(h) x 250(d) mm

1.25 kg

** Design & specification are subject to change without prior notice **

VIH -200K (IR IP Camera)	
Image Pickup Device	1/3" HD Colour CMOS Chipset
Resolution	1 Mp / 720p
Pixels	1280 x 720
Lens	3.6 mm
Video Output	1.0 Vp-p 75ohm (BNC type)
Audio Output	-
Alarm Input / Output	-
Iris Control	A.E.S.
Shutter Mode	-
S/N Ratio	-
Gamma Characteristic	-
Scanning System / Frequency	2:1 Interlace; 15.625KHz (H) x 50Hz (V)
Gain Control / White Balance	Auto
Backlight Mode	Open
Minimum Illumination	0.1 Lux (F1.2, AGC On), 0 Lux (LED on)
Day / Night Function	-
IR Sensitive	Yes
IR LED	36xIR LED (5mm)
IR Coverage / Viewing Range (approximate)	10~15m
Pan / Tilt Angle (approximate)	< Manually adjust >
Pan / Tilt Speed (approximate)	-
Image Masking	-
Aperture Suppress	-
Flickerless	-
Sharpness	-
Built Special Function	Images Flip / Mirror
Network / Remote Control	RJ45, Wifi, DDNS, DHCP, Email, FTP
Presets	Address : 0~255
Users	1*Admin; 7*Normal users
Video Resolution & Speed	1280*720/ 640*360/ 320*180 : 1~25fps
Image Quality	Very High/ High/ Normal/ Low/ Very Low
Power Supply & Consumption	DC12V 1A
Operation Temperature & Humidity	-20°C ~ +50°C ; RH 85% (max.)
Storage Temperature	-20°C ~ +60°C ; RH 85% (max.)
Dimension (w/o bracket) (approximate)	68(Φ) x 150(h) mm
Weight (w/o bracket) (approximate)	500 g

** Design & specification are subject to change without prior notice **