



VIH - 201



VIH - 202



VIH - 203

	VIH - 201	VIH - 202	VIH - 203
Image Pickup Device	1/3" HD Colour CMOS Chipset		
Resolution	2 Mp		
Pixels	1600 x 1200		
Lens	3.6 mm	2.8 mm	3.6 mm
Video Output	1.0 Vp-p 75ohm (BNC type)		
Audio Output	-		
Alarm Input / Output	-		
Iris Control	A.E.S.		
Shutter Mode	-		
S/N Ratio	-		
Gamma Characteristic	-		
Scanning System / Frequency	2:1 Interlace; 15.625KHz (H) x 50Hz (V)		
Gain Control / White Balance	Auto		
Backlight Mode	Open		
Minimum Illumination	0.1 Lux (F1.2, AGC On), 0 Lux (LED on)		
Day / Night Function	-		
IR Sensitive	Yes		
IR LED	36xIR LED (5mm)	22xIR LED (5mm)	22xIR LED (5mm)
IR Coverage / Viewing Range (approximate)	10~15m		
Image Masking	4 x Areas		
Sharpness	-		
Built Special Function	Images Flip / Mirror/ Motion trigger alarm/ Pre-Record		
Network / Remote Control	RJ45, Wifi, DDNS, DHCP, Email, FTP		
Presets	Address : 0~255		
Users	1*Admin; 6*Normal users		
Video Resolution & Speed	(Main) 1600*1200/ 1280*720; (Minor) 640*360/ 352*192 : 1~25fps		
Image Quality	Very High/ High/ Normal/ Low/ Very Low		
Power Supply & Consumption	DC12V 1A	DC5V 2A	DC12V 1A
Operation Temperature & Humidity	-20°C ~ +50°C ; RH 85% (max.)		
Storage Temperature	-20°C ~ +60°C ; RH 85% (max.)		
Dimension (w/o bracket) (approximate)	68(Φ) x 150(h) mm	85(w) x 85(h) x 40(d) mm	121(Φ) x 94(h) mm
Weight (w/o bracket) (approximate)	500 g	200 g	400 g