



(Rear View)

	VIK – 01
<i>DVR / Camera Supported (max.)</i>	via (485-to-232 converter) : 512xDVR; via (RS485 AB Line) : 255xSpeedDome, Multiple of DVRs, Control Standalone DVR, SpeedDome, Network SpeedDome, Network Camera, Network Video Recorder/Server
<b>Function</b>	
<i>Presets (max.)</i>	- Depend on camera -
<i>Address of Camera/Controller (max.)</i>	256
<b>Protocol</b>	(DVR) DH1, DH2; (SpeedDome) DH-SD, Pelco-D, Pelco-P, Pelco-D1, Pelco-P1
<b>Baud Rate</b>	2400, 4800, 9600, 19200 bps
<b>Built-in</b>	LCD Display, 3D-Joystick
<b>Communication / Control Port</b>	Network ,RS232, RS485
<i>Transmitting Distance (max.)</i>	1200 m
<b>Power Supply &amp; Consumption</b>	DC12V 1A
<b>Operation Temperature &amp; Humidity</b>	-10°C ~ +55°C ; RH 90% (max.)
<b>Storage Temperature</b>	-20°C ~ +65°C ; RH 90% (max.)
<i>Dimension (approximate)</i>	320(w) x 50(h) x 190(d) mm
<i>Weight (approximate)</i>	2.5 kg