



**30\*IR LED**  
**Coverage up to 25meter**

**POE Ready !!!**



**1080p (2 MegaPixel)**

VIR – 201	
<b>Image Pickup Device</b>	½.8” SONY Exmor HD Colour CMOS Chipset
<b>Resolution</b>	2 Mp
<b>Pixels</b>	1600 x 1200
<b>Lens</b>	3.6 mm
<b>Video Output</b>	1.0 Vp-p 75ohm (BNC type)
<b>Audio Output</b>	-
<b>Alarm Input / Output</b>	-
<b>Iris Control</b>	-
<b>Shutter Mode</b>	-
<b>S/N Ratio</b>	-
<b>Gamma Characteristic</b>	-
<b>Scanning System / Frequency</b>	-
<b>Gain Control / White Balance</b>	-
<b>Backlight Mode</b>	-
<b>Minimum Illumination</b>	0 Lux (LED on)
<b>Day / Night Function</b>	-
<b>IR Sensitive</b>	Yes
<b>IR LED</b>	30xIR LED (5mm)
<b>IR Coverage / Viewing Range (approximate)</b>	15~25m
<b>Image Masking</b>	4 x Areas
<b>Sharpness</b>	-
<b>Built Special Function</b>	POE, OSD, Day/Night, Display Setting, Alarm I/O, Record Strategy, H.264
<b>Network / Remote Control</b>	RJ45, TCPIP, DHCP, PPPoE, FTP, Email, Cloud
<b>Presets</b>	-
<b>Users</b>	Operator (Admin) / Guest
<b>Video Resolution &amp; Speed</b>	[Main] (1080p) 1920*1080, (960p)1280*960, (720p)1280*720, (D1)720*576, (VGA)640*480; [Sub] (D1)720*576, (CIF)360*288, (QCIF)180*144, (VGA)640*480,(QVGA)320*240 Record Speed : 1~25fps
<b>Image Quality</b>	Very High/ High/ Normal/ Low/ Very Low VBR/CBR : 32~4000kbps
<b>Power Supply &amp; Consumption</b>	DC12V 1A
<b>Operation Temperature &amp; Humidity</b>	-20°C ~ +50°C ; RH 85% (max.)
<b>Storage Temperature</b>	-20°C ~ +60°C ; RH 85% (max.)
<b>Dimension (c/w bracket) (approximate)</b>	70(Φ) x 193(h) mm
<b>Weight (c/w bracket) (approximate)</b>	850 g