



POE Ready !!!



1080p (2 MegaPixel)

24*IR LED
Coverage up to 20meter

VIR – 202	
Image Pickup Device	1 /2.8” SONY Exmor HD Colour CMOS Chipset
Resolution	2 Mp
Pixels	1600 x 1200
Lens	3.6 mm
Video Output	1.0 Vp-p 75ohm (BNC type)
Audio Output	-
Alarm Input / Output	-
Iris Control	-
Shutter Mode	-
S/N Ratio	-
Gamma Characteristic	-
Scanning System / Frequency	-
Gain Control / White Balance	-
Backlight Mode	-
Minimum Illumination	0 Lux (LED on)
Day / Night Function	-
IR Sensitive	Yes
IR LED	24xIR LED (5mm)
IR Coverage / Viewing Range (approximate)	10~20m
Image Masking	4 x Areas
Sharpness	-
Built Special Function	POE, OSD, Day/Night, Display Setting, Alarm I/O, Record Strategy, H.264
Network / Remote Control	RJ45, TCPIP, DHCP, PPPoE, FTP, Email, Cloud
Presets	-
Users	Operator (Admin) / Guest
Video Resolution & Speed	[Main] (1080p) 1920*1080, (960p)1280*960, (720p)1280*720, (D1)720*576, (VGA)640*480; [Sub] (D1)720*576, (CIF)360*288, (QCIF)180*144, (VGA)640*480,(QVGA)320*240 Record Speed : 1~25fps
Image Quality	Very High/ High/ Normal/ Low/ Very Low VBR/CBR : 32~4000kbps
Power Supply & Consumption	DC12V 800mA
Operation Temperature & Humidity	-20°C ~ +50°C ; RH 85% (max.)
Storage Temperature	-20°C ~ +60°C ; RH 85% (max.)
Dimension (c/w bracket) (approximate)	112(Φ) x 80(h) mm
Weight (c/w bracket) (approximate)	400 g

** Design & specification are subject to change without prior notice **