

**Built in VGA input,
DVI, S-Video,
Composite, Audio**

**Heavy Duty Metal
Body + Stand**



VLD-KA26

VLD-KA32

| Model | | VLD - KA26 | VLD - KA32 |
|--------------------------|----------------|--|--------------------------|
| LCD Display | | 26" | 32" |
| Viewable Size (mm) | | 575.769 x 323.712 | |
| Pixel Pitch (mm) | | 0.4215(H) x 0.4215(V) | 0.51075(H) x 0.51075(V) |
| Max. Resolution | VGA | 1366 x 768 (WXGA) | |
| | Video | 500 TV Lines | |
| Display Mode | | VGA, DVI, Composite, S-Video | |
| Display colour | | 16.7M | |
| Scanning | | 56.25 ~ 75.029Hz (H), 31.469 ~ 63.981KHz (V) | |
| Signal Connector | | DC Connector, Audio #1 In/Out., Audio #2 In/Out, DVI In, Y/C In/Out., BNC #1 In/Out., BNC #2 In/Out. | |
| Control Panel | | Power Switch, LED Indicator, Mode, Auto, +(Volume increase), -(Volume decrease), Up(Contrast Adjust), Down(Brightness Adjust), OSD Menu | |
| OSD Menu | VGA, DVI, HDMI | Brightness, Contrast, H-position, V-position, Clock, Phase, Colour Temp., User Colour R/G/B, OSD H-pos, OSD V-pos, Volume, Language, PIP size/Pos., PIP/POP, Sub source, PIP size, PIP H-pos, PIP V-pos, Source swap, Recall | |
| | Video | Colour, Tint (NTSC only), Brightness, Contrast, Sharpness, Volume, H-position, Language, Colour Temp., Scan, PIP/POP, Sub source, PIP size, PIP H-pos, PIP V-pos, Source swap, Recall | |
| Contrast Ratio | | 1500 : 1 (typ.) | |
| Brightness | | 500 cd/m ² (typ.) | |
| Response Time Tr / Tf | | 15 ms (typ.) | |
| Viewing Angle | | (L) 88°, (R) 88°, (U) 88°, (D) 88° | |
| Power Supply | | AC100~240V 50/60Hz | |
| Power Consumption | | 100W (max.) | 190W (max.) |
| Operating Condition | | Temperature : 0°C ~ 40°C, Humidity : 10% ~ 90% | |
| Storage Condition | | Temperature : -20°C ~ 60°C, Humidity : 10% ~ 90% | |
| Lamp Life Time | | 60000 hrs. (typ.) | |
| Dimension (mm) (approx.) | | 634(w) x 390(h) x 125(d) | 769(w) x 467(h) x 118(d) |
| Weight | | 11.5 kg | 21 kg |