

**Portable
w/bag**



VLD – 56T



VLD-10M

Model	VLD – 56T	VLD – 10M
LCD Display	5.6" Colour TFT LCD	10.4" Colour TFT LCD (262K)
Resolution	640 (H) x 480 (V)	800 (H) x 600 (V)
Contrast Ratio	500 : 1 (TYP)	500:1 (TYP)
Brightness	200 cd/m ² (TYP)	230 cd/m ² (TYP)
Response Time Tr/Tf	10/ 15ms (Tr+Tf) (TYP)	10/25 ms (Tr+Tf) (TYP)
Display Mode	Video 1, Video 2, Test Pattern	VGA, Video, S-Video
Power Supply	DC 12V, 1.5A	DC12V, 3A
Power Consumption (Approx.)	11.25W (w/o Battery Charger), 19.875W (w/Battery Charger)	12W (max.)
Backup Battery	Li-Po Battery (DC7.4V , 2500mAh); Charge : ~ 2.5 hours, Usage: ~3.5 hours	-
Control	Power, OSD, Volume, Contrast, Brightness, Colour, Tint, Sharpness, Recall, Language	Power, Contrast, Brightness, OSD, Channel Selector: Y/C,A,B
Inputs	2 x Video (composite 1Vp-p 75ohms) (BNC type) 1 x Audio (3.5mm stereo socket)	1 x VGA 1 x BNC 1 x S-VHS
Outputs	1 x Video (composite 1Vp-p 75ohms) (BNC type) 1 x Audio (3.5mm stereo socket)	-
Lam Life Time	20,000 hours	-
Audio Speaker	1W	-
Operating Condition	Temperature : 0°C ~ 40°C	Temperature : 0°C ~ 50°C Humidity: 20% ~ 85%
Storage Condition	Temperature : -10°C ~ 60°C	Temperature : -20°C ~ 60°C Humidity: 10% ~ 90%
Dimension (mm)	190(w) x 126(h) x 44.5(d)	270(w) x 200(h) x 59(d)
Weight	0.62 kg	1.8 kg