



VMB - 01	
<i>Image Pickup Device</i>	1/3" VZOR B/W CCD
<i>Resolution</i>	380 TV Lines
<i>Pixels</i>	500(H) x 582(V)
<i>Lens</i>	3.6 mm
<i>Video Output</i>	1.0 Vp-p 75ohm (BNC type)
<i>Audio Output</i>	-
<i>Alarm Input / Output</i>	-
<i>Iris Control</i>	A.E.S
<i>Shutter Mode</i>	1/50 ~ 1/100,000 sec.
<i>S/N Ratio</i>	≥ 48dB (AGC off)
<i>Gamma Characteristic</i>	0.45
<i>Scanning System & Frequency</i>	625 Lines, 50 Field/sec.
<i>Gain Control & White Balance</i>	Auto
<i>Backlight Mode</i>	Open
<i>Minimum Illumination</i>	0.05 Lux (F:2.0)
<i>Day / Night Function</i>	-
<i>IR Sensitive</i>	-
<i>IR LED</i>	-
<i>IR Coverage / Viewing Range (approximate)</i>	-
<i>Pan / Tilt Angle (approximate)</i>	-
<i>Pan / Tilt Speed (approximate)</i>	-
<i>Image Masking</i>	-
<i>Aperture Suppress</i>	-
<i>Flickerless</i>	-
<i>Sharpness</i>	-
<i>Built Special Function</i>	-
<i>Network / Remote Control</i>	-
<i>Presets</i>	-
<i>Users</i>	-
<i>Video Resolution & Speed</i>	-
<i>Image Quality</i>	-
<i>Power Supply & Consumption</i>	DC12V 110mA
<i>Operation Temperature & Humidity</i>	-10°C ~ +50°C ; RH 95% (max.)
<i>Storage Temperature</i>	-20°C ~ +60°C ; RH 95% (max.)
<i>Dimension (w/o bracket) (approximate)</i>	34(w) x 34(h) x 30(d) mm
<i>Weight (w/o bracket) (approximate)</i>	70 g

** Design & specification are subject to change without prior notice **