



VMP - 71	
Image Pickup Device	1/3" Sony Exview + Effio-E Colour Chipset
Resolution	700 TV Lines
Pixels	976(H) x 582(V)
Lens	3.7 mm Pinhole Lens
Video Output	1.0 Vp-p 75ohm (BNC type)
Audio In / Output	High Sensitivity Mic x1, (Out) RCA(F)x1
Alarm Input / Output	-
Iris Control	A.E.S.
Shutter Mode	1/50 ~ 1/100,000 sec.
S/N Ratio	≥ 52 dB (AGC off)
Gamma Characteristic	0.45
Scanning System / Frequency	2:1 Interlace; 15.625KHz (H) x 50Hz (V)
Gain Control / White Balance	Auto
Backlight Mode	Auto
Minimum Illumination	0.01 Lux (F2.0)
Day / Night Function	-
IR Sensitive	-
IR LED	-
IR Coverage / Viewing Range (approximate)	-
Pan / Tilt Angle (approximate)	-
Pan / Tilt Speed (approximate)	-
Image Masking	-
Aperture Suppress	-
Flickerless	-
Sharpness	-
Built Special Function	Metal Body
Network / Remote Control	-
Presets	-
Users	-
Video Resolution & Speed	-
Image Quality	-
Power Supply & Consumption	DC12V < 500mA
Operation Temperature & Humidity	-10°C ~ +50°C ; RH 85% (max.)
Storage Temperature	-20°C ~ +60°C ; RH 85% (max.)
Dimension (w/o bracket) (approximate)	(Camera) 11(w) x 20(h)x 11(d) mm, (PCB) 40(w) x 12(h)x 32(d) mm, (Mic) 11(Ø) x 20(d) mm
Weight (w/o bracket) (approximate)	100 g

** Design & specification are subject to change without prior notice **