



VNS - 02



VNS - 101



VNS - 11

| Model | VNS-02 | VNS-101 | VNS-11 |
|--|--|---|---|
| Operation type | | - | |
| Video Input / Output | In:1xBNC | In:1xBNC | In:1xBNC, Out:1xBNC |
| Display Mode | | 1ch. | |
| Resolution (max.) | Display: D1,CIF, Record: D1,HD1,CIF,QCIF | Display: HD1,CIF, Record: D1,HD1,CIF,QCIF, VGA, QVGA | Display: D1,CIF,QCIF Record: D1,CIF,QCIF |
| Speed (max.) | Display: 25fps Record: 1~25fps | Display: 25fps Record: 1/2/3/6/12/25fps | Display: 25fps Record: 1/2/3/6/8/12/25fps |
| Playback channel | - | | |
| Record Mode | Motion/ Alarm/ Continuous, Schedule | | |
| Pre / Post Record Duration | - | | |
| Search Mode | Time/Date, Alarm/ Motion/ Local/ Picture | | |
| Video Compression Format | H.264 | | |
| Image Quality | Level: 1 ~ 6 | | |
| Audio Input & Output | In:1xBNC,1xMicIn (3.5mm socket) Out: 1x3.5mm socket | In:1xMicIn (3.5mm socket) Out: 1x3.5mm socket | In:1xRCA Out: 1xRCA |
| Alarm Input & Output | In:4ch.(pin), Out:2ch.(pin)(NO/NC) | In:4ch.(pin), Out:1ch.(pin)(NO/NC) | In:1ch.(pin), Out:1ch.(pin)(NO/NC) |
| Motion Detection Area & Sensitivity | Area: 22x18, Sensitivity: 6 Levels | Area: 16x12, Sensitivity: 6 Levels | 9 Area: 43x29, Sensitivity: 9 Levels |
| Privacy Masking | - | | |
| Console Function | Email, Rec, PTZ presets, Video pop-up, Listen Alarm, Relay output | | Email, Rec, Relay output |
| Hardisc Bay | - | | |
| USB Interface | - | | |
| CDRW / DVDRW | - | | |
| PTZ Protocol | 51 types | 51 types | Pelco-D, Pelco-P, Panasonic |
| Network & Control Interface | RS-485 | RS-485, RS-232 | RS-485 |
| Network Function | TCP/IP, HTTP, PPPoE, DDNS, DHCP, SMTP, Telnet | | |
| Remote Software | I.E. | | |
| Power Supply & Consumption | DC12V 3.3A | | DC5V 1A |
| Operation Temperature & Humidity | 0°C ~ 50°C (20%~80%) | | |
| Dimension (approximate) | 162(w) x 30(h) x 136(d) mm | | 107(w) x 29(h) x 98(d) mm |
| Weight (w/o Hardisc) (approximate) | 650 g | | 430 g |