



VS-3060



VY-3939W



VYA-3040

VYD-3040

	VS-3060	VY-3939W	VYA-3040	VYD-3040
Power Supply	AC24V 38W	AC24V 10W	AC24V 30W	AC24V 30W
Installation Environment	Indoor / Outdoor	Indoor	Indoor / Outdoor	Indoor / Outdoor
Pan Tilt Speed	Pan: 9°/sec. Tilt: 4°/sec	Pan: >=5.1°/sec. Tilt: >=3.6°/sec	Pan: >=7.5°/sec. Tilt: >=6°/sec	Pan: >=7.5°/sec. Tilt: >=6°/sec
Pan Tilt Angle	Pan: 0~355°, Tilt: -90° ~ +10°	Pan: 0° ~355° Tilt: +10° ~ -60°	Pan: 0~355° Tilt: +6° ~ -90°	Pan: 0~355° Tilt: +6° ~ -90°
Built-in	Decoder, Heater, Address: 0~256, Baud Rate: 2400 ~ 192000bps, Protocol: 4 types	Cable for PTZ camera	Cable for PTZ camera	Decoder, Heater, Address: 0~256, Baud Rate: 2400 ~ 192000bps, Protocol: 4 types
Max. Load (approximate)	15 kg	2.5 kg	10 kg	10 kg
Material	Aluminium Alloy	ABS Plastic	Zinc Alloy	Zinc Alloy
Dimension (approximate)	214(w)* 289(h)* 290(d)mm	132(w)* 127(h)* 274(d)mm	169(w)* 222(h)* 189(d)mm	169(w)* 222(h)* 189(d)mm
Weight (approximate)	9.5 kg	1.4 kg	4.2 kg	4.2 kg

** Design & specification are subject to change without prior notice **