



VR - 03



VR - 102

	VR - 03	VR - 102
<b>Image Pickup Device</b>	1/3" VZOR Colour CCD	1/3" SONY SuperHAD Colour CCD
<b>Resolution</b>	420 TV Lines	430 TV Lines
<b>Pixels</b>	500(H) x 582(V)	
<b>Lens</b>	6 mm	
<b>Video Output</b>	1.0 Vp-p 75ohm (BNC type)	
<b>Audio Output</b>	-	
<b>Alarm Input / Output</b>	-	
<b>Iris Control</b>	A.E.S.	
<b>Shutter Mode</b>	1/50 ~ 1/100,000 sec.	
<b>S/N Ratio</b>	≥ 48dB (AGC off)	
<b>Gamma Characteristic</b>	0.45	
<b>Scanning System / Frequency</b>	2:1 Interlace; 15.625KHz (H) x 50Hz (V)	
<b>Gain Control / White Balance</b>	Auto	
<b>Backlight Mode</b>	Open	
<b>Minimum Illumination</b>	0.8 Lux (LED off), 0 Lux (LED on) (F:2.0)	0.5 Lux (LED off), 0 Lux (LED on) (F:2.0)
<b>Day / Night Function</b>	Yes	
<b>IR Sensitive</b>	Yes	
<b>IR LED</b>	28xIR LED (5mm)	
<b>IR Coverage / Viewing Range (approximate)</b>	15~25m	
<b>Pan / Tilt Angle (approximate)</b>	-	
<b>Pan / Tilt Speed (approximate)</b>	-	
<b>Image Masking</b>	-	
<b>Aperture Suppress</b>	-	
<b>Flickerless</b>	-	
<b>Sharpness</b>	-	
<b>Built Special Function</b>	-	
<b>Network / Remote Control</b>	-	
<b>Presets</b>	-	
<b>Users</b>	-	
<b>Video Resolution &amp; Speed</b>	-	
<b>Image Quality</b>	-	
<b>Power Supply &amp; Consumption</b>	DC12V 1000mA	
<b>Operation Temperature &amp; Humidity</b>	-10°C ~ +50°C ; RH 95% (max.)	
<b>Storage Temperature</b>	-20°C ~ +60°C ; RH 95% (max.)	
<b>Dimension (w/o bracket) (approximate)</b>	70(w) x 66(h) x 120(d) mm	
<b>Weight (w/o bracket) (approximate)</b>	440 g	

\*\* Design & specification are subject to change without prior notice \*\*