



	VR - 071	VR - 171
<b>Image Pickup Device</b>	1/3" SONY Super Exview II + Effio Colour DSP	
<b>Resolution</b>	700 TV Lines	
<b>Pixels</b>	537(H) x 597(V)	
<b>Lens</b>	3.6 mm	
<b>Video Output</b>	1.0 Vp-p 75ohm (BNC type)	
<b>Audio Output</b>	-	
<b>Alarm Input / Output</b>	-	
<b>Iris Control</b>	A.E.S.	
<b>Shutter Mode</b>	1/50 ~ 1/120,000 sec.	
<b>S/N Ratio</b>	≥ 50dB (AGC off)	
<b>Gamma Characteristic</b>	0.45	
<b>Scanning System / Frequency</b>	625 Lines, 50 fields/sec.	
<b>Gain Control / White Balance</b>	A.G.C / Auto(3200~10,000°K)( 0 Colour Rolling)	
<b>Backlight Mode</b>	-	
<b>Minimum Illumination</b>	0.3 Lux (LED off), 0 Lux (LED on) (F1.2)	
<b>Day / Night Function</b>	Yes	
<b>IR Sensitive</b>	Yes	
<b>IR LED</b>	24xIR LED (5mm)	36xIR LED (5mm)
<b>IR Coverage / Viewing Range (approximate)</b>	10~15m	10~25m
<b>Pan / Tilt Angle (approximate)</b>	Pan : 0~360°, Tilt : 45~100°	Pan : 0~270°, Tilt : 0~90°
<b>Pan / Tilt Speed (approximate)</b>	-	
<b>Image Masking</b>	-	
<b>Aperture Suppress</b>	-	
<b>Flickerless</b>	-	
<b>Sharpness</b>	-	
<b>Built Special Function</b>	ABS Plastic Body	Aluminium Alloy Body
<b>Network / Remote Control</b>	-	
<b>Presets</b>	-	
<b>Users</b>	-	
<b>Video Resolution &amp; Speed</b>	-	
<b>Image Quality</b>	-	
<b>Power Supply &amp; Consumption</b>	DC12V 800mA	
<b>Operation Temperature &amp; Humidity</b>	-20°C ~ +50°C ; RH 85% (max.)	
<b>Storage Temperature</b>	-20°C ~ +60°C ; RH 85% (max.)	
<b>Dimension (w/o bracket) (approximate)</b>	92(Φ) x 70(h) mm	70(Φ) x 130(h) mm
<b>Weight (w/o bracket) (approximate)</b>	100 g	500 g

\*\* Design & specification are subject to change without prior notice \*\*