



|  | VR - 071C                                      |
|--|--|
| <b>Image Pickup Device</b>                       | 1/4" HD CMOS Colour DSP                        |
| <b>Resolution</b>                                | 800 TV Lines                                   |
| <b>Pixels</b>                                    | 976(H) x 582(V)                                |
| <b>Lens</b>                                      | 3.6 mm   |
| <b>Video Output</b>                              | 1.0 Vp-p 75ohm (BNC type)                      |
| <b>Audio Output</b>                              | -  |
| <b>Alarm Input / Output</b>                      | -  |
| <b>Iris Control</b>                              | A.E.S.   |
| <b>Shutter Mode</b>                              | 1/50 ~ 1/120,000 sec.                          |
| <b>S/N Ratio</b>                                 | 48 dB (AGC off)                                |
| <b>Gamma Characteristic</b>                      | 0.45   |
| <b>Scanning System / Frequency</b>               | 625 Lines, 50 fields/sec.                      |
| <b>Gain Control / White Balance</b>              | A.G.C / Auto(3200~10,000°K)( 0 Colour Rolling) |
| <b>Backlight Mode</b>                            | -  |
| <b>Minimum Illumination</b>                      | 0.8 Lux (LED off), 0 Lux (LED on) (F1.2)       |
| <b>Day / Night Function</b>                      | Yes  |
| <b>IR Sensitive</b>                              | Yes  |
| <b>IR LED</b>                                    | 24xIR LED (5mm)                                |
| <b>IR Coverage / Viewing Range (approximate)</b> | 10~15m   |
| <b>Pan / Tilt Angle (approximate)</b>            | Pan : 0~360°, Tilt : 45~100°                   |
| <b>Pan / Tilt Speed (approximate)</b>            | -  |
| <b>Image Masking</b>                             | -  |
| <b>Motion Detect</b>                             | -  |
| <b>D-WDR</b>                                     | -  |
| <b>2DNR</b>                                      | -  |
| <b>Built Special Function</b>                    | ABS Plastic Body                               |
| <b>Network / Remote Control</b>                  | -  |
| <b>Presets</b>                                   | -  |
| <b>Users</b>                                     | -  |
| <b>Video Resolution &amp; Speed</b>              | -  |
| <b>Image Quality</b>                             | -  |
| <b>Power Supply &amp; Consumption</b>            | DC12V 800mA                                    |
| <b>Operation Temperature &amp; Humidity</b>      | -20°C ~ +50°C ; RH 85% (max.)                  |
| <b>Storage Temperature</b>                       | -20°C ~ +60°C ; RH 85% (max.)                  |
| <b>Dimension (w/o bracket) (approximate)</b>     | 92(Φ) x 70(h) mm                               |
| <b>Weight (w/o bracket) (approximate)</b>        | 100 g  |

\*\* Design & specification are subject to change without prior notice \*\*