



c/w OSD Control Key

	VR - 072C
<b>Image Pickup Device</b>	1/3" SONY Super Exview II + Effio Colour DSP
<b>Resolution</b>	700 TV Lines
<b>Pixels</b>	537(H) x 597(V)
<b>Lens</b>	4 mm ; <b>Type:</b> Manual/DC/Video
<b>Video Output</b>	1.0 Vp-p 75ohm (BNC type)
<b>Audio Output</b>	-
<b>Alarm Input / Output</b>	-
<b>Iris Control</b>	<b>Mode:</b> Auto/Close/Open ; <b>Speed:</b> 0~255
<b>Shutter Mode</b>	Auto/Auto+Shut, Brightness: 0~255, <b>Low Luminance:</b> AGC/Off, Brightness: ~255
<b>S/N Ratio</b>	≥ 50dB (AGC off)
<b>Gamma Characteristic</b>	0.45
<b>Scanning System / Frequency</b>	625 Lines, 50 fields/sec.
<b>Gain Control / White Balance</b>	ATW/ Push/ User1/ User2/ Anti CR/ Manual/ Push Lock
<b>Backlight Mode</b>	Off/ BLC/ HLC
<b>Minimum Illumination</b>	0.05 Lux (LED off), 0 Lux (LED on) (F1.2)
<b>Day / Night Function</b>	Auto/ Colour/ B/W
<b>IR Sensitive</b>	Yes
<b>IR LED</b>	30xIR LED (5mm)
<b>IR Coverage / Viewing Range (approximate)</b>	10~15m
<b>Pan / Tilt Angle (approximate)</b>	Pan : 0~90° ,Tilt : 0~90°
<b>Pan / Tilt Speed (approximate)</b>	-
<b>Image Masking</b>	<b>8xAreas:</b> Top/Bottom/Left/Right/Transparency/Mosaic/Colour
<b>Motion Detect</b>	4xAreas : Top/Bottom:0~288, Left/Right:0~468 Sensitivity : 0~127, Block Display
<b>D-WDR</b>	Off/ On: Luminance:High/Mid/Low, Contrast:High/Mid/Low
<b>2DNR</b>	Off/ Y:0~15/ C:0~15/ Y/C(0~15)
<b>Built Special Function</b>	OSD Control, Language: 8 types, Camera ID, Adjust ABS Plastic Body
<b>Network / Remote Control</b>	-
<b>Presets</b>	-
<b>Users</b>	-
<b>Video Resolution &amp; Speed</b>	-
<b>Image Quality</b>	-
<b>Power Supply &amp; Consumption</b>	< DC12V 500mA
<b>Operation Temperature &amp; Humidity</b>	-20°C ~ +50°C ; RH 85% (max.)
<b>Storage Temperature</b>	-20°C ~ +60°C ; RH 85% (max.)
<b>Dimension (w/o bracket) (approximate)</b>	126(Φ) x 100(h) mm
<b>Weight (w/o bracket) (approximate)</b>	360 g