



	VR – 082
<b>Image Pickup Device</b>	1/3" Sony Exmor Colour Sensor
<b>Resolution</b>	1000 TV Lines
<b>Pixels</b>	1280(H) x 960(V)
<b>Lens</b>	2.8 ~ 12 mm
<b>Video Output</b>	1.0 Vp-p 75ohm (BNC type)
<b>Audio Output</b>	-
<b>Alarm Input / Output</b>	-
<b>Iris Control</b>	A.E.S.
<b>Shutter Mode</b>	1/50 ~ 1/100,000 sec.
<b>S/N Ratio</b>	≥ 48 dB (AGC off)
<b>Gamma Characteristic</b>	0.45
<b>Scanning System / Frequency</b>	2:1 Interlace; 15.625KHz (H) x 50Hz (V)
<b>Gain Control / White Balance</b>	Auto
<b>Backlight Mode</b>	Open
<b>Minimum Illumination</b>	0.05 Lux (F1.2, AGC On), 0 Lux (LED on)
<b>Day / Night Function</b>	-
<b>IR Sensitive</b>	Yes
<b>IR LED</b>	72xIR LED (5mm)
<b>IR Coverage / Viewing Range (approximate)</b>	20~70m
<b>Pan / Tilt Angle (approximate)</b>	(Manual) Pan : 0~180°, Tilt : 0~90°
<b>Pan / Tilt Speed (approximate)</b>	-
<b>Image Masking</b>	-
<b>Aperture Suppress</b>	-
<b>Flickerless</b>	-
<b>Sharpness</b>	-
<b>Built Special Function</b>	Metal Body
<b>Network / Remote Control</b>	-
<b>Presets</b>	-
<b>Users</b>	-
<b>Video Resolution &amp; Speed</b>	-
<b>Image Quality</b>	-
<b>Power Supply &amp; Consumption</b>	DC12V 1000mA
<b>Operation Temperature &amp; Humidity</b>	-30°C ~ +50°C ; RH 85% (max.)
<b>Storage Temperature</b>	-30°C ~ +60°C ; RH 85% (max.)
<b>Dimension (w/o bracket) (approximate)</b>	100(Φ) x 152(d) mm
<b>Weight (w/o bracket) (approximate)</b>	800 g

\*\* Design & specification are subject to change without prior notice \*\*