



VR – 112Q	
Image Pickup Device	1/3" SONY Super HAD II Colour DSP CCD
Resolution	570 TV Lines
Pixels	752(H) x 582(V)
Lens	6 mm
Video Output	1.0 Vp-p 75ohm (BNC type)
Audio Output	-
Alarm Input / Output	-
Iris Control	A.E.S.
Shutter Mode	1/50 ~ 1/100,000 sec.
S/N Ratio	≥ 50dB (AGC off)
Gamma Characteristic	0.45
Scanning System / Frequency	2:1 Interlace
Gain Control / White Balance	Auto
Backlight Mode	Open
Minimum Illumination	0.5 Lux (F2.0); 0 Lux (LED on)
Day / Night Function	Yes
IR Sensitive	Yes
IR LED	35xIR LED (5mm)
IR Coverage / Viewing Range (approximate)	20~30m
Pan / Tilt Angle (approximate)	-
Pan / Tilt Speed (approximate)	-
Image Masking	-
Aperture Suppress	-
Flickerless	-
Sharpness	-
Built Special Function	-
Network / Remote Control	-
Presets	-
Users	-
Video Resolution & Speed	-
Image Quality	-
Power Supply & Consumption	DC12V 800mA
Operation Temperature & Humidity	-10°C ~ +50°C ; RH 95% (max.)
Storage Temperature	-20°C ~ +60°C ; RH 95% (max.)
Dimension (w/o bracket) (approximate)	88(w) x 72(h) x 115(d) mm
Weight (w/o bracket) (approximate)	410 g

** Design & specification are subject to change without prior notice **