



| VR – 66X   |  |
|--|--|
| <b>Image Pickup Device</b>                       | 1/3" SHARP Colour Super CCD + 12 bit DSP |
| <b>Resolution</b>                                | 540 TV Lines                             |
| <b>Pixels</b>                                    | 752(H) x 582(V)                          |
| <b>Lens</b>                                      | 4 ~9 mm                                  |
| <b>Video Output</b>                              | 1.0 Vp-p 75ohm (BNC type)                |
| <b>Audio Output</b>                              | -  |
| <b>Alarm Input / Output</b>                      | -  |
| <b>Iris Control</b>                              | Manual Iris                              |
| <b>Shutter Mode</b>                              | 1/50 ~ 1/100,000 sec.                    |
| <b>S/N Ratio</b>                                 | > 50dB (AGC off)                         |
| <b>Gamma Characteristic</b>                      | 0.45                                     |
| <b>Scanning System / Frequency</b>               | 2:1 Interlace                            |
| <b>Gain Control / White Balance</b>              | Auto                                     |
| <b>Backlight Mode</b>                            | -  |
| <b>Minimum Illumination</b>                      | 0 Lux (LED on)                           |
| <b>Day / Night Function</b>                      | Yes                                      |
| <b>IR Sensitive</b>                              | Yes                                      |
| <b>IR LED</b>                                    | 35xIR LED (8mm)                          |
| <b>IR Coverage / Viewing Range (approximate)</b> | 40~60m                                   |
| <b>Pan / Tilt Angle (approximate)</b>            | -  |
| <b>Pan / Tilt Speed (approximate)</b>            | -  |
| <b>Image Masking</b>                             | -  |
| <b>Aperture Suppress</b>                         | -  |
| <b>Flickerless</b>                               | -  |
| <b>Sharpness</b>                                 | -  |
| <b>Built Special Function</b>                    | -  |
| <b>Network / Remote Control</b>                  | -  |
| <b>Presets</b>                                   | -  |
| <b>Users</b>                                     | -  |
| <b>Video Resolution &amp; Speed</b>              | -  |
| <b>Image Quality</b>                             | -  |
| <b>Power Supply &amp; Consumption</b>            | DC12V 1000mA                             |
| <b>Operation Temperature &amp; Humidity</b>      | -10°C ~ +45°C ; RH 95% (max.)            |
| <b>Storage Temperature</b>                       | -30°C ~ +60°C ; RH 95% (max.)            |
| <b>Dimension (w/o bracket) (approximate)</b>     | 95(w) x 90(h) x 150(d) mm                |
| <b>Weight (w/o bracket) (approximate)</b>        | 800 g                                    |

\*\* Design & specification are subject to change without prior notice \*\*