



VSD - 71



VK - 1000

Model	VSD - 71	VK - 1000
Pickup Sensor	1/4" Colour SONY SuperHAD	-
Lens	3x Optical Zoom (f=2.8 ~ 7.3mm)	-
Resolution	380 TV Lines	-
Minimum Illumination	0.5 Lux (F2.0)	-
Picture Pixels	PAL : 310,000	-
Pan Tilt Angle	Pan : 0 ~ 355°, Tilt : 0 ~ 90°	-
Pan Tilt Speed	8 ~ 80°/sec.	-
Back Light	Auto	-
White Balance	Auto / 2500o ~ 9500oK	-
Sync Mode	Internal	-
S/N Ratio	> 48dB	-
Electronic Shutter	PAL : 1/50 ~ 1/110,000 sec.	-
Power Supply	DC 12V 1A	DC 12V 400mA
Baud Rate	2400 / 4800 / 9600 bps	
Communication Distance	800 / 1000 / 1200	
Cameras' ID can be set & controlled	256 units	100 units
Preset positions	32 (w/o grouping), 64 (total in 4 groups)	12 positions
Preset Groups	4 groups (each group 16 positions) (only for protocol : EYEVIEW)	
IR LED	17*IR LED	-
IR Coverage	5 ~ 10m	-
Protocol	PELCO-D2400, PELCO-P4800, PELCO-P9600, EYEVIEW-9600	
Operation Temperature	-10°C ~ +50°C	
Communication input	RS-485	
Dimension (approx.)	100(o) x 130(h) mm	250(w) x 40(h) x 120(d) mm
Weight	1 kg	600 g