

10" Colour LCD Monitor



VS – GP030302

| | VS – GP030302 | |
|-----------------------------------|--|---|
| <i>Display size</i> | 800 x 600 | |
| <i>Pixel pitch</i> | 0.264 mm | |
| <i>Viewing angle</i> | (H) 120° , (V) 120° | |
| <i>Luminance</i> | 230cd/m ² | |
| <i>Contrast ratio</i> | 300 | |
| <i>Response time</i> | 25 ms | |
| <i>Frequency</i> | (H) 30~61KHz, (V) 6~75KHz | |
| <i>Display Colour</i> | 262,144 colours | |
| <i>Maximum mode</i> | 1024 x 768 @ 75Hz | |
| <i>Sync. video signal</i> | H/V separate, TTL,P or N.0.7Vp-p @75Ω | |
| <i>Colour system</i> | PAL / NTSC4.43 / NTSC3.58 / SECAM | |
| <i>Sound system</i> | BG / DK / I / M | |
| <i>Video input</i> | 1.0Vp-p @ 75Ω | 3.5mm socket w/Stereo AV input (RCA type), 1x PC~VGA input |
| <i>Audio input</i> | 500mVrms | |
| <i>Power input</i> | DC 12V | |
| <i>Power consumption</i> | 9W | |
| <i>Power saving</i> | < 1 W | |
| <i>Operating temperature</i> | 10°C ~ 40°C (50°F ~ 104°C) | |
| <i>Operating humidity</i> | 10% ~ 80% | |
| <i>Storage temperature</i> | -25°C ~ +45°C (-13°F ~ +113°F) | |
| <i>Storage humidity</i> | 5% ~ 95% | |
| <i>Speaker output</i> | 2W (max.), 16Ω | |
| <i>Headphone output</i> | 10mW (max.) 3.5mm Stereo socket, 32Ω | |
| <i>Frequency Response (RF,AV)</i> | (RF) 80Hz ~15KHz, (AV) 80Hz ~ 20KHz; at -3dB | |
| <i>Dimension</i> | 243(w) x 208(h) x 40(d) mm | |
| <i>Weight</i> | 900 g | |

** Design & specification are subject to change without prior notice **