



VZ - 707	
Image Pickup Device	1/4" SONY SuperHAD Colour CCD
Resolution	535 TV Lines
Pixels	752(H) x 582(V)
Lens	36x Optical Zoom Lens (f=3.6~129.6,F1.6~4.2)
Video Output	1.0 Vp-p 75ohm (BNC type)
Audio Output	-
Alarm Input / Output	-
Iris Control	Auto
Shutter Mode	AI, AE, Manual Mode:- Shutter: 1/50~1/100K; Iris:F1.6~1.8; AGC:5/ 13/ 22/ 30dB > 50dB (AGC off)
S/N Ratio	0.45
Gamma Characteristic	0.45
Scanning System & Frequency	625 Lines, 50 Field/sec.
Gain Control & White Balance	AGC : (selectable), WBC : (Push/ Auto/ Outdoor/ Fluorescent/ Indoor/Manual) Off / Sens:Gain(0~255) / 5 Areas: Unweighted Level(0~15)
Backlight Mode	0.8 Lux (F1.6, 1/50sec.)
Minimum Illumination	Auto / Day / Night / EXT
Day / Night Function	-
IR Sensitive	-
IR LED	-
IR Coverage / Viewing Range (approximate)	-
Pan / Tilt Angle (approximate)	-
Pan / Tilt Speed (approximate)	-
Image Masking	8x Areas (Adjustable H. & V position – same colour for all areas (Hold/Grey/White/Black/Red/Orange/Yellow/Green/Blue/Purple)
Aperture Suppress	On / Off
Flickerless	Off / Normal / LLFL / FIXS
Sharpness	Off / Low / Mid / High
Built Special Function	O.S.D, Camera-ID(0~255), Mirror effect(On/Off), Anti-Colour Rolling(On/Off), Colour Suppress(Off/On:Low/Mid/High), High Resolution(On/Off), High Light Suppress(0~3),Threshold Level(0~3), Focus Mode(Normal,INTV,ZMTR,Manual)
Network / Remote Control	RS-485, Baud Rate(1200/ 2400/ 4800/ 9600/ 19200)
Presets	-
Users	-
Video Resolution & Speed	-
Image Quality	-
Power Supply & Consumption	DC12V 400mA
Operation Temperature & Humidity	0°C ~ +50°C ; RH 95% (max.)
Storage Temperature	-20°C ~ +60°C ; RH 95% (max.)
Dimension (w/o bracket) (approximate)	60(w) x 60(h) x 113(d) mm
Weight (w/o bracket) (approximate)	400 g

** Design & specification are subject to change without prior notice **