



High Definition Industrial Camera



Model	WAT-120N	WAT-221S	WAT-232	WAT-250D	WAT-300DH3
Pickup Device	1/2" Interline Transfer B/W CCD	1/2" Interline Transfer Colour CCD	1/3" Interline Transfer Colour CCD	1/3" Interline Transfer Colour CCD	1/3" Interline Transfer B/W CCD
Lens	-	-	-	-	2.9 mm Auto Iris
Resolution	570 TV Lines	450 TV Lines	450 TV Lines	450 TV Lines	570 TV Lines
Min.Illumination	0.00002 Lux(F1.2)	0.1 Lux(F1.2)	0.1Lux/0.006 Lux(F1.2)	0.1 Lux(F1.2)	0.04 Lux(F2.0)
Other Feature	Mini size,Ultra Low Lux, Ultra Hi-Resolution	Mini size,Low Lux, Hi-Resolution	Mini, Super Low Lux, DayNight,Hi-Resolution	Mini size,Low Lux, Hi-Resolution	Very Low Lux, Ultra Hi-Resolution



Model	WAT-502B	WAT-902DM3-S	WAT-902H2	WAT-240F	WAT-240RA
Pickup Device	1/3" Interline Transfer B/W CCD	1/3" Interline Transfer B/W CCD	1/2" Interline Transfer B/W CCD	1/4" Interline Transfer Colour CCD	1/4" Interline Transfer Colour CCD
Lens	-	-	-	3.8 mm	3.8 mm
Resolution	400 TV Lines	570 TV Lines	570 TV Lines	350 TV Lines	350 TV Lines
Min.Illumination	0.003 Lux(F1.4)	.00012 Lux(F1.4)	0.0003 Lux(F1.4)	0.4 Lux(F2.0)	0.4 Lux(F2.0)
Other Feature	Mini size, Super Low Lux	Mini size,Ultra Hi-Res., Extra Low Lux	Mini size,ExtraLowLux, Ultra Hi-Resolution	Flexible gooseneck	-



Model	WAT-704R				
Pickup Device	1/4" Interline Transfer Colour CCD				
Lens	3.8 mm				
Resolution	380 TV Lines				
Min.Illumination	0.08 Lux(F2.0)				
Other Feature	Very Low Lux				



Model	21HC	35HB	3745B-5	300SV	AD-603
Iris type	Manual Iris	Manual Iris	Pinhole	-	-
Focal Length	50 mm	35 mm	3.7 mm	-	-
Lens Type	1/2"	1/2"	1/2"	Sunvisor for WAT-300DH	Power supply for WAT-240RA, DC5V

* All box cameras not include with lens unless mentioned.

** Design & specification are subject to change without prior notice **